

SECTION 02952**CONTINGENT PATCHING EXISTING PAVEMENT BITUMINOUS CONCRETE,
PORTLAND CEMENT CONCRETE****02952.01 GENERAL****A. Description**

Contingent materials for patching existing pavement shall be furnished and placed only where, when, and in the amounts directed by the Engineer. The work shall include furnishing and installing bituminous concrete and/or Portland cement concrete pavement in accordance with the Contract Documents.

B. Related Work Included Elsewhere

1. Bituminous Concrete Pavement installation; Section 02641.
2. Portland Cement Concrete pavement installation; Section 02651.

C. Quality Assurance

1. Quality assurance for bituminous concrete shall be as specified in Section 02641.01.
2. Quality assurance for Portland cement concrete shall be as specified in Section 03310.01.

D. Submittals

1. Submittals for bituminous concrete shall be as specified in Section 02641.01.
2. Submittals for Portland cement concrete shall be as specified in Section 03310.01.

02952.02 MATERIALS**A. Materials Furnished by the County**

The County will not furnish any materials for patching existing pavement.

B. Contractor's Options

None.

C. Detailed Material Requirements

1. Detailed material requirements for bituminous concrete shall be as specified in Section 02641.02.
2. Detailed material requirements for Portland cement concrete shall be as specified in Section 02680.03.

02952.03 EXECUTION

Execution shall be as specified in Section 02680.03.

02952.04 METHOD OF MEASUREMENT

Measurement for furnishing and installing bituminous concrete and/or Portland cement concrete for patching existing pavement will be made on the basis of the area of pavement patch for a specified depth. The area will be based on the trench widths shown on the Standard Details, or as detailed in the Contract Documents for the particular size and type of utility being installed, or as directed by the Engineer.

Where the use of double sheeting is permitted by the Engineer in an excavation, the width used in calculating the area for applicable contingent items associated with the pavement patch shall be based on the contract trench width plus three feet. The granting of permission to utilize double sheeting shall be solely at the discretion of the Engineer; and if the Contractor elects to use this method without permission, no additional payment width will be allowed.

02952.05 BASIS OF PAYMENT

A. General

1. Payment will be made at the bid or fixed prices stipulated in the Proposal. The payments will include and cover furnishing all labor, tools, equipment, and materials necessary to complete the work as directed and accepted by the Engineer in accordance with the Contract Documents.
2. Payment will be made only for materials, which are utilized at the direction of the Engineer beyond the areas disturbed by the Contractor, his subcontractors, or suppliers. No payment will be made for quantities required to bring trench surfaces back to grade due to settlement within the maintenance period or beyond the limits shown on the Standard Details or in excess of those ordered by the Engineer.

**CONTINGENT PATCHING EXISTING PAVEMENT
BITUMINOUS CONCRETE, PORTLAND CEMENT
CONCRETE**

02952-3 of 3

B. Bituminous Concrete

Payment for furnishing and installing bituminous concrete or patching existing pavement will be made at the price bid per ton. Payment will include removing temporary surfacing and placing and compacting of graded aggregate as required.

C. Portland Cement Concrete

Payment for furnishing and installing Portland cement concrete for patching existing pavement will be made per square yard for the specified depth. Payment will include removing temporary surfacing and placing and compacting graded aggregate as required.

END OF SECTION